

Cox Sales Company  
2035 Cook Drive  
Salem, VA 24153 USA  
Phone: (540) 345-2636 FAX: (540) 342-8684

## TECHNICAL DATA SHEET

**PRODUCT DESIGNATION:** 4483

**PRODUCT FEATURES:** Aggressive tack, good pot stability, low odor

**SUGGESTED USE:** Pressure Sensitive Adhesive

## TYPICAL PROPERTIES

<b>TYPE:</b> Hot Melt Polymer Blend	<b>PH:</b> N/A
<b>SOLIDS:</b> 100%	<b>FLAMMABILITY:</b> N/A
<b>F&amp;DA STATUS:</b> 175.105	<b>EFFECT FROM FREEZING:</b> None
<b>WEIGHT PER GALLON:</b> 8.4 lbs.	<b>STORAGE LIFE:</b> 1 year
<b>COLOR:</b> amber	<b>THIN WITH:</b> Heat
<b>ODOR:</b> Low Resin	<b>VISCOSITY:</b> 1900 cps. @ 350°F
<b>CLEAN WITH:</b> HEAT, SCRAPER, PARAFFIN WAX	

**SUGGESTED SURFACE PREPARATION:** All surfaces should be clean and dry, free of dust, dirt, grease, and any other foreign materials.

- This product is heat stable for 100 hours @ 350°F
- Suggested application temperature range: 325-350°F

**METHOD OF APPLICATION:** CONVENTIONAL HOT MELT EQUIPMENT