

**Cox Sales Company**  
**2035 Cook Drive**  
**Salem, Virginia 24153 USA**  
**Phone: (540) 345-2636**  
**FAX: (540) 342-8684**

## **COX-3550 PRESSURE SENSITIVE ADHESIVE**

**COX-3550** is an extremely versatile pressure-sensitive adhesive emulsion. Aggressive dry tack and adheres to a wide variety of treated and untreated surfaces. Extreme Dry Tack. Excellent laminating adhesive for film to paper,

### **TYPICAL EMULSION PROPERTIES:**

DESCRIPTION:	LIQUID PSA
COLOR:	WHITE (FILM DRIES CLEAR)
SOLIDS CONTENT %:	50.0 – 54.0
VISCOSITY (CPS @ 25°C, 20 rpm):	1,200 – 2,000
pH VALUE:	4.0 – 7.0
ODOR:	SLIGHT (CHARACTERISTIC)
POUNDS PER GALLON:	8.2
FLAMMABILITY CLASSIFICATION:	NON-HAZARDOUS

### **TYPICAL PERFORMANCE PROPERTIES:**

PEEL ADHESION, STAINLESS STEEL (20 min. DWELL):	1500 g/25 mm
HOLDING POWER (1"x1"x1000gms @ 40°C):	6 to 60 min.

### **TYPICAL HANDLING AND APPLICATION:**

STORAGE LIFE:	6 MONTHS
STORE IN:	BUILDING AT AMBIENT TEMP.
DILUTION:	WATER
CLEAN UP WITH:	WATER (WET), SOLVENT (DRY)
FREEZE THAW STABLE:	NO (PROTECT FROM FREEZING)

### **FDA STATUS:**

The formulation of **COX-3550** complies with F.D.A. Regulations concerning Food Packaging Adhesives/ F.D.A. Status 21CFR175.105 and 21CFR175.125 "Adhesives:".